

WORLD TOP SECURITY - Kodicom DN-68232

PC based 32 Channel DVR

400/400FPS

Main features

32 channel high resolution high quality • real time image display and record using MPEG4 compression

Powerful and user friendly operating • software

Easy maintenance and configuration using • just a network connection

Multiple PTZ protocols are including • various speed dome camera types

Motion tracking enabling a speed dome • camera to track moving objects

Intelligent search options including index • and object search

Remote site monitoring possibility using • the CMS software through a network connection

Multiple user levels & various backup • options

Alarms including remote function using • the CMS software

Ideal Applications

Premium DVR surveillance•

Schools, Museums, Banks•

Road and Retail installations•



The Kodicom DN-68232 is the benchmark for all PC platform DVR's. This well established, ultra stable product is a must for any large surveillance system.

Rammed with the latest features there are many ways this DVR out performs its standalone counterparts.

Search functionality could not be easier as an object search mode allows you to paint the screen, and thus any movement on the recordings in that area will be highlighted, and searching is then as easy as clicking a thumbnail. If you wish to search by event, the time bar will highlight all alarm and recorded activity

Subsequent pictures can be cleaned up using the picture sharpening function on the stills menu.

Remote view and alarms can be seen via the CMS software also enabling remote PTZ control. New software functionally also allows viewing via a PDA.

The DN-68232 represents the must have for any serious surveillance application.



Data Sheet - Kodicom DN 68232

PC based 32 channel DVR

400/400 fps pre-fitted with 250Gb HDD

Specifications (all specs subject to modification)

	Model	DN-68232
Display	Speed	NTSC : 480 fps PAL : 400 fps
	Screen Division	1, 4, 9, 10, 16, 33, 36 way screen division
Recording	Max Speed (@CIF) Resolution	NTSC : 480 fps PAL : 400 fps NTSC : 640 x 480, 320 x 240, 160 x 120
	Video	PAL : 768 x 576, 384 x 288, 192 x 144
Audio	Recording Option	Continuous, Motion, Sensor and Pre-Alarm
	Format	NTSC / PAL
	CODEC	MPEG4
	Input Output	32 Channel VGA
Alarm	Input	8 Channel (Line input)
	Output	1 Channel
Network	CODEC	G. 726 (8kHz Mono)
	Input	16 Ports
Backup	Output	16 Ports
	Transmission	Ethernet (RJ-45)
Other Functions	Protocol	TCP/IP (Dynamic IP is supported)
	Device	USB, CD-RW, Network, DVD-RW (optional)
	Remote Control	CMS (remote monitoring software)
Other Functions	Remote Alarm	E-mail, CMS report
	PTZ	RS232C, RS485
	W/D	Yes
	Function	
	Image Authentication	Watermark
	Language	17 Languages
	Password	Multi-Level User Password Authorization
	USB	6 Port (USB 2.0)
	Working Temperature	0°C - 50°C
	Power Source	100 -240 Vac 50/60Hz
Dimensions	430mm(W) x 176mm(H) x 460mm(D) 18.5 Kg	