

IDA APPROVED 2.4GHz WIRE + WIRELESS WIFI IP COLOUR CAMERA. VIEWABLE ON INTERNET IE, FIREFOX, IPHONE, CMS Functions. Viewable Total Darkness with Night Vision - 0 Lux. Pan Tilt controllable.



IPPT250

- * Embedded linux system IP Camera
- * 32Bit RSIC Processor
- * Motion-JPEG
- * 10pcs IR LED, IR distance 10m.

Model	IPPT250 IP Camera
Operation system	Embedded linux operation system
Image sensor	32Bit RSIC Embedded Processor
Compression	Motion-JPEG
Frame ratio	25fps
Image display	Brightness contrast chroma saturation
Minimal Illumination	0.1 Lux/F1.2
S/N ratio	>48DB (Auto)
Shutter speed	1/50s(1/60s) ~ 1/100,000 s
Backlight compensation	Auto
Night vision	10pcs 5# IR LED, IR Distance 10m

Audio Processor	Built-in two-way voice audio processor, support sound monitor
Audio	AGC
Pan/ Title range	Pan horizontal rotation: 220 degrees Tilt vertical rotation: 0 - 90 degrees
Pan/ Title speed	Pan horizontal rotation: 15 degrees/second Tilt vertical rotation: 15 degrees/second
Internet interface	RJ-45, 10/100MB Ethernet network
Network protocol	TCP/IP HTTP ICMP DHCP FTP SMTP PPP
User numbers	15, meanwhile
IP mode	dynamic or static IP address, PPPOE
Indoor/ outdoor	Indoor service
Power consumption	DC5V 2A
Wifi	WIFI,802.11 b/g
Camera lens	standard: 3.6mm select: 6mm 8mm
IP mode	dynamic or static IP address, PPPOE
Material	Alloy-zinc
Indoor/ outdoor	Wireless gun type, indoor service
TRANSMITTING FREQUENCY	2.4GHz
RF OUTPUT POWER	50mW
Temperature	Operating:-10°C~+50 °C Storage:-20°C~+50°C
Power	DC12V,2000mA
Humidity	95% RH
Dimension	105mm×110mm (Φ×H)
Weight	250g