

## **WLA2G QUICK INSTALLATION:**

Thank you for purchasing our product.

- 1) Insert DC12V Regulated only.

### **Basic Arm & Dis-Arm**

- 2) Press Arm / Lock, trigger Motion Detector or Door Sensor, Siren activated.
- 3) Press Dis-Arm / Unlock First time, Siren shut down.
- 4) Press Dis-Arm / Unlock Second time, Zone Light shut off.

### **Program Telephone Number**

- 5) Link Tel Line to Control Panel Right, Link Dial Telephone to Control Panel Left.
- 6) Press Y & Arm sametime, Y Light ON (pg 16)
- 7) # 1 # TELEPHONE NUMBER # (1 for first Telephone number to dial out)
- 8) # 1 # \* TELEPHONE NUMBER # (\* Delay dial for 0 or 9 outside connection, pg20)
- 9) Press Dis-Arm to Exit.

### **Record Message**

- 10) Press & Hold Mic icon, record 10 seconds of Urgent message. (pg21)

### **Add Accessories**

- 11) Press STAR icon, trigger / ARM New Accessories.
- 12) Dis-arm, Arm again, trigger New Accessories, Control Panel should activate. (pg24)

### **Delay Arm & Dis-Arm**

- 13) Press Y & Arm sametime, Y Light ON (pg 16)
- 14) \* 2 \* 1 \* (1 – 1 min, pg18 )
- 15) \* 2 \* 0 \* ( Instant)
- 16) Press Dis-Arm to Exit.

Please refer to Main Menu for more details instructions / functions.

Hope you will enjoy our Affordable Professional Product.

JUN 2008